# Sel-O-Fit Bits **★**



#### 1/4" Hex Insert Bits

Part	Point	Overall I	Length
Number	Size	ln.	mm
440-1-SFX	1	1	25
440-2-SFX	2	1	25
440-215-SFX	2	1 1/2	38
440-22-SFX	2	2	51
440-225-SFX	2	2 1/2	64
440-3-SFX	3	1	25



#### 1/4" Hex Insert Bits – Limited Clearance



Part	Point	Overall Length		Turned Le	ength (A)	Turned OD (B)	
Number	Size	ln.	mm	ln.	mm	ln.	mm
446-2-SFX	2	1	25	7/16	11	0.18	4.6




#### 5/16" Hex Insert Bits

Part	Point	Overall Length	
Number	Size	ln. mm	
480-2-SFX	2	1 1/4 32	



#### 1/4" Hex Power Drive



Part	Point	Overall Length		Body Di	Body Diameter		Length
Number	Size	In.	mm	ln.	mm	In.	mm
491-SFX	1	1 15/16	49	3/16	5	1 1/4	32
491-A-SFX	1	2 3/4	70	3/16	5	2	51
491-B-SFX	1	3 1/2	89	3/16	5	2 3/4	70
491-C-SFX	1	6	152	3/16	5	2	51
492-SFX	2	1 15/16	49	1/4	6	1 1/4	32
492-A-SFX	2	2 3/4	70	1/4	6	2	51
492-B-SFX	2	3 1/2	89	1/4	6	2 3/4	70
492-C-SFX	2	6	152	1/4	6	2	51

Sel-O-Fit® bits are designed to provide a more efficient means of driving Pozidriv® screws.

The Sel-O-Fit bit places torque on the strongest and most mechanically advantageous portion of the driver tip.

This allows more torque to be applied while minimizing the possibility of breakage and camout.

Sel-O-Fit® is a registered trademark of Cooper Industries.

## Quadrex® Bits 🔷

#### 1/4" Hex Insert Bits

Part	Point	Overall Length		
Number	Size	In.	mm	
950-QD-2	2	1	25	

### 1/4" Hex Power Drive

Part	Point	Overall Length		Body Diameter		Turned Length	
Number	Size	In.	mm	In.	mm	In.	mm
95-QD-2	2	1 15/16	49	1/4	6	1 1/4	32
95-A-QD-2	2	2 3/4	70	1/4	6	2	51
95-B-QD-2	2	3 1/2	89	1/4	6	2 3/4	70
95-QD-3	3	1 15/16	49	5/16	7.9	1 1/4	32

If the tool you need does not appear in this catalog, give us a call. The odds are, we may have what you need as a non-catalog item. If not, our experienced staff of tooling experts can design and manufacture "specials" to meet the needs of your specific application. Give us a call at 1-800-845-5629 or visit our website **www.apex-tools.com**.